

MÓDULO LED P4.81 OUTDOOR 250X250MM



Pixel Pitch	4.81 mm
Pixel Configuration	1R1G1B/SMD1921
Moduel Size(L×W)mm	250mm×250mm
Module Resolution	52*52 dot
Driving Method	1/ 13 Scan
Refresh Rate	3840 Hz
Brightness	5000 nit/m²
Contrast	1000:1
Brightness Adjustment	Auto and Manual
Power Consumption	Max Power: <40W
	Average power: <20W
Color Temperature	3200K—13000K
Horizontal Viewing Angle	140°
Vertical Viewing Angle	140°
Signal Processing	10 - 14bit
Grey Processing	1024×1024×1024 16834×16834×16834
Control Distance	Cable100m, Multimode500m, Single mode 2km
Frame Frequency	60 Hz
Control Mode	Synchronous
MTBF	≥10000 Hours
Life Span	≥ 100000 Hours
Remote Control	Can realize remote control and send alarm signal to operators in case of failure logging (Be customized)
Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
Power Supply	AC 110V/ 220V (Be Customized)
Protection	waterproof, dustproof, high temperature pervention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)